



WIRELESS TURN SIGNAL MIRROR GENERAL INSTALLATION INSTRUCTIONS

CIPA PART #49900

TO INSTALL BATTERIES

1. Unscrew mirror counter-clockwise from base to open mirror.
2. Remove circuit board and install 3 AAA batteries onto base on circuit board.
3. Replace circuit board onto mirror base, and replace mirror.

EXAMPLE OF UNDER-DASH INSTALLATION

1. Remove dashboard panel under steering wheel.
2. Locate Ignition/ACC wire.
3. Locate both turn signal wires.
4. Attach Black (Ground) wire to bare metal surface.
5. Splice Brown wire from module to Right Turn Signal wire.
6. Splice Orange wire from module to Left Turn Signal wire.
7. Splice Red wire from module to Ignition/ACC wire.
8. Clean vehicle's sideview mirrors and remove protective tape backing from adhesive on rear of Wireless Turn Signal Mirrors and place on vehicle mirrors with firm pressure for 30 seconds.
9. Secure module underneath dashboard.
10. Replace dashboard panel underneath steering wheel.

PROFESSIONAL INSTALLATION IS RECOMMENDED FOR THIS PRODUCT

ESTIMATED INSTALLATION TIME: 20-30 MINUTES

INFORMATION TO USER

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures.

- Reorient or relocate the existing antenna
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.